



Check list for reclaiming of gas mixtures with C4-FN

Authorization number: (is assigned by DILO as soon as measured values are known)	Customer: _____
--	-----------------

Total order	≤ 50 l	> 50 l – 600 l
Total number of containers		
Total weight of gas mixtures in kg		
Tare weight in kg		

Bottle / container number	
Filling quantity per container in kg	
CO [ppm]. Maximum 5000 ppm for acceptance according to EfbV under 160505.	
Known measured values/more precise contents of gas components (if available)	
Previous application of the gas (e.g. insulating gas in GIS)	
Share C4-FN [Mol-%]	
Option	
Dew point [°C atm.]	
Carrier gas CO ₂ /N ₂ /Synt. Air	
Filling pressure/temperature [bara/°C]	

Packing

Quantity / Type of packaging _____

Dimensions in cm _____

Total weight of package in kg _____

The cylinders must be fastened by wedges and fixed in a safe and suitable way as to avoid moving or falling over

ATTENTION
Tanks as from 450 liters must be marked on two opposite sides with dangerous goods mark!

Labelling? UN1080 UN3163 no label

Only one UN-Label per container!

TÜV-validity of the cylinders? _____

Colour of cylinder neck Green Yellow Grey

Loading facilities (forklift trucks) available on site? Yes No

Shipper's obligations are acknowledged and taken into account

Where was the gas used? High voltage Medium voltage Low voltage

Used in voltage level? _____

.....
Date

.....
Signature (customer)